




SOLID SHINE Series

3-Chip DLP™ Laser light source models
Lens not included with 3-Chip DLP™ models.






	PT-RQ50K	50,000 lm 51,000 lm (Center)	Native 4K ¹	4K	4K	GeoPro
	PT-RQ35K	30,500 lm 32,000 lm (Center)	4K	4K	4K	GeoPro
	PT-RZ34K	30,500 lm 32,000 lm (Center)	WUXGA ²	4K	4K	GeoPro
Available from CY2022 40 ³						
	PT-RQ25K	20,000 lm	4K ²	4K	4K	GeoPro
	PT-RZ24K	20,000 lm	WUXGA	4K	4K	GeoPro
	PT-RQ18K	16,000 lm	4K ²	4K	4K	GeoPro
	PT-RZ17K	16,000 lm	WUXGA	4K	4K	GeoPro
	PT-RQ22K	20,000 lm 21,000 lm (Center)	4K ⁴	4K	4K	GeoPro
	PT-RZ21K	20,000 lm 21,000 lm (Center)	WUXGA	DIGITAL LINK	4K	GeoPro
	PT-RS20K	20,000 lm 21,000 lm (Center)	SXGA+	DIGITAL LINK	4K	GeoPro
	PT-RZ16K⁵	16,000 lm 16,800 lm (Center)	WUXGA	DIGITAL LINK	4K	GeoPro
	PT-RQ13K	10,000 lm	4K ⁴	4K	4K	GeoPro
	PT-RZ12K	12,000 lm	WUXGA	DIGITAL LINK	4K	GeoPro

Large-Venue


Installation

Short Throw

LCD Lamp based models

	PT-EZ770Z/L	6,500 lm	WUXGA	DIGITAL LINK	4K	GeoPro
	PT-EW730Z/L	7,000 lm	WXGA	DIGITAL LINK	4K	GeoPro
	PT-EX800Z/L	7,500 lm	XGA	DIGITAL LINK	4K	GeoPro
	PT-EZ590/L	5,400 lm	WUXGA	DIGITAL LINK	4K	GeoPro
	PT-EW650/L	5,800 lm	WXGA	DIGITAL LINK	4K	GeoPro
	PT-EW550/L	5,000 lm	WXGA	DIGITAL LINK	4K	GeoPro
	PT-EX620/L	6,200 lm	XGA	DIGITAL LINK	4K	GeoPro
	PT-EX520/L	5,300 lm	XGA	DIGITAL LINK	4K	GeoPro
	PT-FZ570	4,500 lm	WUXGA	DIGITAL LINK	4K	GeoPro
	PT-FW530	4,500 lm	WXGA	DIGITAL LINK	4K	GeoPro
	PT-FX500	5,000 lm	XGA	DIGITAL LINK	4K	GeoPro

LCD Lamp based models





	PT-TW381R	3,300 lm	WXGA	DIGITAL LINK	4K	GeoPro
	PT-TW380	3,300 lm	WXGA	DIGITAL LINK	4K	GeoPro
	PT-TX440³	3,800 lm	XGA	DIGITAL LINK	4K	GeoPro
	PT-TX350³	3,200 lm	XGA	DIGITAL LINK	4K	GeoPro

Featured image: PT-TW381R

Installation

Portable

1-Chip DLP™ Laser light source models
Lens not included with 'L' models.

	PT-RCQ10/L	10,000 lm 10,500 lm (Center)	2715 x 1697 dots ⁶	4K	4K	GeoPro
	PT-RCQ80/L	8,000 lm 8,400 lm (Center)	2715 x 1697 dots ⁶	4K	4K	GeoPro
	PT-RZ120/L	12,000 lm 12,600 lm (Center)	WUXGA	4K	4K	GeoPro
	PT-RZ990/L	9,400 lm 10,000 lm (Center)	WUXGA	4K	4K	GeoPro
	PT-RZ890/L	8,500 lm 8,800 lm (Center)	WUXGA	4K	4K	GeoPro
	PT-RZ790/L	7,000 lm 7,200 lm (Center)	WUXGA	4K	4K	GeoPro
	PT-RZ690/L	6,000 lm 6,200 lm (Center)	WUXGA	4K	4K	GeoPro
DLP SOLID SHINE LASER 360°						
1-Chip DLP™ Laser light source models (Lens fixed)						
	PT-FRQ60	6,000 lm 6,200 lm (Center)	4K ⁸	4K	4K	GeoPro
	PT-FRQ50	5,200 lm 5,400 lm (Center)	4K ⁸	4K	4K	GeoPro
	PT-FRZ60	6,000 lm 6,200 lm (Center)	WUXGA	4K	4K	GeoPro
	PT-FRZ50	5,200 lm 5,400 lm (Center)	WUXGA	4K	4K	GeoPro
	PT-FRZ55³	5,000 lm 5,200 lm (Center)	WUXGA	4K	4K	GeoPro

Installation

Portable

Short Throw

LCD Laser light source models
Available from CY2023 10³

	PT-MZ20KL	20,000 lm	WUXGA	4K	4K	GeoPro
	PT-MZ16KL	16,000 lm	WUXGA	4K	4K	GeoPro
	PT-MZ13KL	13,000 lm	WUXGA	4K	4K	GeoPro
	PT-MZ10KL	10,000 lm	WUXGA	4K	4K	GeoPro
	PT-MZ880	8,000 lm	WUXGA	4K	4K	GeoPro
	PT-MZ780	7,000 lm	WUXGA	4K	4K	GeoPro
	PT-MZ680	6,000 lm	WUXGA	4K	4K	GeoPro




LCD Laser light source models (Lens fixed)

	PT-VMZ71⁵	7,000 lm	WUXGA	4K	4K	GeoPro
	PT-VMZ61⁵	6,200 lm	WUXGA	4K	4K	GeoPro
	PT-VMZ51	5,200 lm	WUXGA	4K	4K	GeoPro
	PT-VMZ51S	5,200 lm	WUXGA	4K	4K	GeoPro
	PT-VMZ41	4,500 lm	WUXGA	4K	4K	GeoPro
	PT-VMW61	6,200 lm	WXGA	4K	4K	GeoPro
	PT-VMW51	5,200 lm	WXGA	4K	4K	GeoPro

Available from CY2022 30³

	PT-LMZ460	4,600 lm	WUXGA	4K	4K	GeoPro
	PT-LMZ420	4,200 lm	WUXGA	4K	4K	GeoPro
	PT-LMW460	4,600 lm	WXGA	4K	4K	GeoPro
	PT-LMW420	4,200 lm	WXGA	4K	4K	GeoPro
	PT-LMX460	4,600 lm	XGA	4K	4K	GeoPro
	PT-LMX420	4,200 lm	XGA	4K	4K	GeoPro

LCD Laser light source models (Lens fixed)
Available from CY2022 30³

	PT-TMZ400	4,000 lm	WUXGA	4K	4K	GeoPro
	PT-TMW380	3,800 lm	WXGA	4K	4K	GeoPro
	PT-TMX380	3,800 lm	XGA	4K	4K	GeoPro

1: Resolution 4096 x 2160 Pixels. 2: Resolution 3840 x 2400 Pixels [Quad Pixel Drive: ON]. 3: The availability varies depending on the country. 4: Resolution 5120 x 3200 Pixels [Quad Pixel Drive: ON]. 5: Available in U.S./Canada/Latin America/Japan only. For more information regarding availability in Latin American countries or regions, please contact your local sales representative. 6: With Smooth Pixel Drive ON. 7: HDMI/DIGITAL LINK input only. 8: Resolution 3840 x 2160 Pixels [With Quad Pixel Drive]. 9: HDMI/DIGITAL LINK input only. Supports signals up to 4K/30p. 10: HDMI input only. Supports signals up to 4K/30p. 11: To operate wireless projection, the optional Wireless Module AJ-WM50 is required. 12: To operate wireless projection, the optional Wireless Module ET-WML100 (Stock limited)/AJ-WM50 is required. * Available in black/white cabinet. The projector is able to emulate the same control commands of most previous Panasonic projectors when it is replacing. Note: [L] Lens-less model. The specifications are subject to change without notice. For more information, please visit the website >> panasonic.net/cns/projector/